Wired JUGS Pro-Sports Radar Gun Interface Cable Wiring Diagram

Alzatex. Inc. 6400 SW 213th Ave Aloha, OR 97007 www.alzatex.com terryl@alzatex.com 503 642-9693

Hard Wired connection to connect the R2050 radar gun to the R2022A Radar Gun Display.

Designed by Terry Lang

Cable Specifications: Length: 50 feet Type: 4 cond, 22GA, stranded, CM/CL2 Color: White

Connectors: P1 - Hirose SR-30 series 4 pin metal 10mm miniature microphone connector Hirose SR30-10PE-4P

Mates to connector on the radar gun: Hirose SR30-10R-4S

Conxall- 6382-4PG-3DC Installable plug 4 position, 16GA, solder cup ST cable end 4 terminal 4 port step boot



THE JUGS GUN



BK=GND

RD=+V





Rear View of Male Hirose Connector

(Solder Side)

Wired Radar Gun Cable JUGS Pro-Sports Radar Gun Interface Cable to connect the R2050 radar gun to the R2022A radar gun display.

Label:

Green

Front View of Male Connector

Yellow or White WH=D

Black

Red=NC

Green = NC

GN=D+

Rear View of Female Conxall Connector (Solder Side)

Conxall- 6382-4PG-3DC



Alzatex Part Number R2022A-50F-DAT